D705MLG

Indoor Public Display

Key Features

- 70" LCD TFT public display
- out-of-home media panel
- tempered glass
- 1920 x 1080 resolution
- 2000:1 high contrast
- 600 cd/m² high brightness
- 178° (h/v) wide viewing angle
- array of connectors
- metal frame housing
- built-in video wall function
- portrait/landscape orientation
- auto cooling system
- remote control & maintenance

D705MLG – Tempered Glass Type

Since the mid-90s, the name HYUNDAI has been synonymous with the design and production of state-of-the-art display technologies. Advanced devices offering sophisticated design and supreme image quality – with "built-in" future-proofing.

By using special "Out-Of-Home" LCD panels HYUNDAI IT's indoor public displays ensure the presentation of digital signage contents in a pin sharp, high bright and brilliant picture quality. Meeting all necessary technical requirements for professional display equipment these enhanced displays ensure a reliable and failure-free operation in any kind of indoor environment. In addition, a tempered security glass protects the screen against vandalism.

Display Solutions by Expertise.

HYUNDAI

Display Panel		Panel Technology	LCD | S-PVA TFT
		Screen Size (inch | cm)	70" | 177,8
		Active Display Area (mm)	1549.44 x 871.56
		Number of Pixels	1920 x 1080 (WUXGA)
		Aspect Ratio	16 : 9
		Display Colors	16.7 Mil.
		Brightness (cd/m²)/(typ)	600
		Contrast Ratio	2000 : 1
		Response Time (ms, GTG)	8
		Viewing Angle (H/V)	178°/178°
		Life Time	50,000h
		Housing	black powder coated metal
Resolution		Monitor	1920 x 1080
		DTV (without tuner)	1080p
Connectivity & Control	Input	VGA (15pin D-Sub)	1
		HDMI	1
		Composite | Component (BNC)	1 | 1
		Audio: PC | Component | Composite	1 | 1 | 1
		RS232C	1
	Output	VGA (15pin D-Sub)	1
		DVI (Connected type HDMI)	1
		Composite | Component (BNC)	1 | 1
		RS-232C	1
		Speaker (ready)	1
	Integrated Video Wall Function (Multi-Screen)		HDMI, VGA (15pin D-Sub), Component (BNC), Composite (BNC)
	Power Requirement	Input Voltage	100 – 240VAC
		Consumption (typ) (W)	800
		DPMS (W)	6
	Auto Cooling System		Yes (3EA)
	Auto Power Control (DPMS)		yes (optional set-up)
Feature	Tempered Glass		yes
	Touch Screen		Option (Model: D705MLI)
Mechanical	Dimension (mm)	Set (W x H x L) (mm)	1683.4 x 1005.4 x 153.4
		Bezel Size (U/D/L/R) (mm)	63/63/63/63
		Packed (W x D x H) (mm)	1810 x 1134 x 272
		Wall Mounting Hole (W x H mm)	600 x 200, 600 x 400
	Weight (kg)	Set (kg)	95
		Packed (kg)	120
Approvals	EMI/EMC | Safety		FCC, CE | cTUVus, TUV, CB
Environmental Conditions	Temperature | Humidity		0° – 40° | 20% – 80%
OSD Languages			10
Accessories			power cord, HDMI cable, D-Sub cable, user manual, remote control
Warranty			Standard: 2 years, less than 18 hours usage per day
EAN Code			880 909 374 609 1



Mechanical Drawing

Technical details are subject to change without further notice. Errors excepted. Version: as of December 2009.

Hyundai IT Europe GmbH • P.O. Box 1268 • 65234 Hochheim, Germany
Tel. +49 (0) 6146 904-0 • Fax +49 (0) 6146 904-110 • E-Mail info@hyundaiIT.eu